

AFL4-W08-EHL

IEI Light Industrial Panel PC

Powered by Intel® Elkhart Lake Platform



WWW.IEIWORLD.COM




AFL4-W08-EHL

Fanless panel PC with narrow bezel design, Intel® Celeron® J6412 processor, on-board 8GB memory, HDMI output, 2.5GbE LAN, two RS-232/422/485, two USB 3.2 Gen2, one USB 2.0, one M.2 M key expansion slot, and anti-glare & anti-UV 10-point touchscreen




Intel® Celeron® J6412 SoC

Intel® Elkhart Lake low power SoC, adopting 10nm process, 4-core 4-thread, 2.00GHz base frequency and up to 2.60GHz burst frequency



Support 4K UHD Display Output

10th generation Intel® Ultra HD graphics engine allows the system to display video and images in stunning 4K resolution over HDMI 1.4b.



Anti-glare and Anti-UV PCAP

With anti-glare and anti-UV coating, the 10-point touchscreen provides clear display without reflection.



Works with Gloves and Water

The equipped capacitive touch screen supports gloved operation and waterproof function that can effectively eliminate false touch operating caused by water spray



Extensive I/O Interfaces

The panel PC is small, but comes with abundant I/O for a variety of application scenarios. It includes two UART, three USB, one 2.5G network port and one HDMI interface.




Support WiFi 6E and Bluetooth 5.2


Strong Wi-Fi 6E wireless network capability provides more bandwidth, and the low latency Bluetooth 5.2 connection is more stable and consumes less power.









Fully Integrated I/O



Block Diagram



Dimensions (Unit: mm)



Specifications

Model		AFL4-W08-EHL
LCD	Size	8" (16:10)
	Resolution (WxH)	1280 x 800
	Brightness (cd/m²)	420
	LCD Color	16.7M
	Pixel Pitch (mm)	0.135 x 0.135
	Contrast Ratio	800:1
	Viewing Angle (H-V)	170°/170°
	Backlight MTBF	30000 hours
Touch	Touch Screen	PCAP with USB interface (anti-UV/AG coating)
	Touch Controller	EETI EXC 81 Series
Mainboard	SOC	Intel® Celeron® Processor J6412 1.5M Cache, up to 2.60 GHz / TDP 10W
	RAM	Dual channel 8GB LPDDR4x on board (up to 16GB)
	Ethernet	LAN1: Intel® I226-V 2.5GbE controller
	Audio Codec	Realtek ALC888S
	Storage	128G eMMC (optional)
	Expansion	1 x M.2 2242 M key (PCIe Gen3 x1 + SATA)
	I/O Ports & Switch	2 x RS-232/422/485 by DB9 1 x 2.5GbE LAN 2 x USB 3.2 Gen2 1 x USB2.0 1 x HDMI output 1 x 12V DC Jack 1 x Power button 1 x Reset button 1 x AT/ATX switch
Audio		AMP 1.2 W (internal speaker)
Wireless & Bluetooth		IEEE 802.11 a/b/g/n/ax, Bluetooth V5.2 1 x M.2 2230 A Key Slot (PCIe + USB signal)
Physical	Body Material	Aluminum die casting+SECC
	Mounting	Wall, Stand, ARM, VESA 75
	Color	Silver+Black
Environment	Operating Temperature (°C) (Ambient with air flow)	-10 ~ 50@50%RH
	Storage Temperature (°C)	-20 ~ 60@50%RH
	Humidity	10% to 90%@40°C (non-condensing)
	Operating Shock	Half-sine wave shock 5G; 11ms; 100 shocks per axis
	Operating Vibration	MIL-STD-810G 514.5C-1 (with SSD)
	IP Level	Front panel IP64
	Safety&EMC	CE/EMC, UKCA, FCC, RED (Class A)
	Power Consumption	12V@3.06A
ErP		ErP 2009/125/EC
OS		Windows 10/11 IoT/Linux
Net Weight		0.98kg

Packing List

Item	Q'ty
Power cord	1
Power adapter	1
QIG	1

Ordering Information

Part No.	Description
AFL4-W08-EHL-J1/8G-R11	8" 420cd/m² 1280x800 fanless Panel PC with Intel® Celeron® Processor J6412 (10W) on-board Processor, 8GB LPDDR4 on-board, 802.11a/b/g/n/ac/ax WiFi&Bluetooth®5.2 module, PCAP touch,R11

Options

Item	Part No.	Description
Stand	STAND-C12-R10	VESA 75/100 Easy Stand
V-Stand	VSTAND-A07-R12*	Stand V Type for AFL series, VESA 75/100
Wall	AFLWK-12*	Monitor Wall mounting kit
OS	AFL4-EHL-W10IoT21-E	OS Image with Windows® 10 Enterprise Entry 64-bit 2021 LTSC for all AFL4-X-EHL Series
	AFL4-EHL-W11IoT24-E	OS Image with Windows® 11 IoT Enterprise Entry 64-bit 2024 LTSC for all AFL4-XXX-EHL Series

*This material number has MOQ requirements. For specific details, please contact the business sales channel.