

Rear Mount LCD

Wide Temperature Range LCD

8.4"

Specifications

RoHS
COMPLIANT
2011/65/EU

Model Name	R08T200-RMT1WT
Viewable Size Image	8.4"
Active Display Area(mm)	170.4(H)x127.8(V)
Pixel Pitch(mm)	0.213(H)x0.213(V)
Number of Pixels	800x600
Contrast Ratio	600:1(typ.)
Display Color	16.2M(8-bit)
Brightness(cd/m ²)	450
Viewing Angle(CR>=10)	-75~75(H);-75~75(V)(typ.)
Synchronization Range	31.5~46.9KHz/60~75Hz
Horizontal/Vertical	
Recommended Resolution	800x600@60Hz,75Hz
Signal Connector	15 pin D-Sub
Power Source	12V DC in, with External AC to DC Adapter (100~240V AC)
Power Consumption	15W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	S-Video, Composite
Optional DVI Input	No
Optional Touch Screen	Resistive, SAW
System Operating temp	-20°C~60°C
Storage temperature	-20°C~70°C

Remarks: R08L200 series= VGA input only

R08L230 series= VGA+Video Input



Mechanical Drawing

