


Workstation Industriali

Serie GOI-200 - Chassis per SBC 1.3



Workstation Industriale 2U
Doppio HDD estraibile SATA/SAS
Configurato su richiesta
Burn in climatico su ogni apparato
Test Report di collaudo



Chassis


IP-204- Rev.31

Dimensioni	Chassis 2U - 483 x 88 x 450 mm
Montaggio	Rack 19"
Materiale	Acciaio pre-zincato
Architettura	Backplane passivo PICMG 1.3
Varianti	• GOI-200-EBP: Chassis colore nero per backplane passivo PICMG 1.3 EBP-D5E2 versione per HDD / SSD / SATA • GOI-200-GO: Chassis colore nero per backplane passivo PICMG 1.3 GO-N2UP5 versione per HDD / SSD / SATA
Drives	1 x media slim 5.25"; 2 x HDD 3.5" SATA/SAS removibili
Ventilazione	3 x ventole 80mm (= 42.5 CFM cad.)
Filtri	1 filtro per l'aria lavabile
Led sul fronte	LED per Power e funzionalità HDD
Pulsanti	Power On/Off e System Reset
Fronte	Porta drives con viti imperdibili, connettore PS2, e USB
Retro	Alloggiamento per 6 bracket full size
Colore	Nero o altri colori su richiesta
Shock	15g durata 11ms - EN 60068-2-27
Vibrazioni	10-150Hz: 1G - EN 60068-2-6
Umidità	10 - 95% non condensata
Temperatura	Operativa 0°C... +50°C Storage -20°C... +70°C


Complementi

Storage	• Doppio cassetto estraibile per HDD / SSD / M.2 • Soluzioni SATA / SAS
Media	• Masterizzatore DVD • Tastiera beige/nera italiana/inglese • Mouse ottico
Schede I/O	• Ethernet Server Adapter • GPGPU / Schede Video • Schede Multi-Head • Schede I/O Analogiche e Digitali • Schede FPGA • Schede MULTISERIALI • Frame Grabber • MIL-1553 / ARINC 429 / ARINC 418
Guide	Guide telescopiche per montaggio a rack
Sistemi Operativi	• Windows® versioni Enterprise / Embedded • Windows® versioni Server • Linux

Fronte



Retro



Single Board: ROBO-8115VG2AR

CPU Preferred	• W-1290E: 10C 3.5 GHz • W-1270E: 8C 3.4 GHz • W-1250: 6C 3.3 GHz • W-1250P: 6C 4.1 GHz • W-1290: 10C 3.2 GHz • W-1290P: 10C
Chipset	Intel W480E
RAM	DDR4 2666 SDRAM 4x DIMM, max 128GB
Graphics	Triple independent displays by VGA on bracket (1920x1200 @ 60Hz) DVI-I on bracket (1920x1200 @ 60Hz) (VGA + DVI-D on bracket by DVI-I port) HDMI on board (4096x2160 @ 30Hz)
Ethernet	2 GbE
SATA ports	5 x SATA 600 (support RAID 0, 1, 5, 10)
M.2 slots	1x M.2 Type M 2280 (on bottom side)
USB	4x USB 2.0 ports 4x USB 3.2 Gen 2 ports on board 2x USB 3.2 Gen 2 ports on bracket
COM	2x RS232 2x RS-232/422/485 selectable
KB/MS	1x 10 pin box header for external
Other	Audio, on board programmable Digital I/O
TPM	Yes
I/O Bracket	2 x USB 3.2, 2x GbE, 1 x DVI-I



Backplane



EBP-D5E2

1 x PICMG CPU, 1 x PCI-E x16,
1 x PCI-E x4, 2 x PCI



GO-N2UP5

1 x PICMG CPU, 1 x PCI-E x1,
1 x PCI-E x16, 2 x PCI

Alimentatori

AC



EN 62368

FSP600-80PSA
PS2 Single 600W

Output					
+3.3V	+5V	+12V	-5V	-12V	+5VSB
25A	25A	16A	0.1A	0.5A	4A
Input					
90~264VAC Full Range					
MTBF					
100.000 h					
Dimensioni					
150x86x140 mm					

AC



EN 62368

Z-HG2-5600V
PS2 Single 600W

Output					
+3.3V	+5V	+12V	-5V	-12V	+5VSB
25A	25A	45A	-	0.8A	3.5A
Input					
100~240VAC Full Range					
MTBF					
171.848 h					
Dimensioni					
150x86x140 mm					

AC



EN 62368

Z-MRPS2-500-2AC
PS2 Redundant 500W

Output					
+3.3V	+5V	+12V	-5V	-12V	+5VSB
20A	20A	40A	0.3A	0.5A	3A
Input					
90V~264VAC					
MTBF					
>100.000 h					
Dimensioni					
150x84x190 mm					



DC



EN 62368

BES-540C
PS2 Single 400W 24VDC

Output					
+3.3V	+5V	+12V	-5V	-12V	+5VSB
25A	25A	30A	-	0.8A	3.5A
Input					
20VDC...36VDC					
MTBF					
121.000 h					
Dimensioni					
150x86x140 mm					

DC



Z-BMRW-5360V4V
PS2 Redundant 360W 24VDC

Output					
+3.3V	+5V	+12V	-5V	-12V	+5VSB
25A	25A	28A	-	0.8A	3.5A
Input					
18VDC...36VDC					
MTBF					
125.331 h					
Dimensioni					
150x86x185 mm					

DC



EN 62368

BES-540T
PS2 Single 400W -48VDC

Output					
+3.3V	+5V	+12V	-5V	-12V	+5VSB
25A	25A	32A	-	0.8A	3.5A
Input					
-36VDC...-72VDC					
MTBF					
143.878 h					
Dimensioni					
150x86x140 mm					

DC



Z-DMRW-5600V4V
PS2 Redundant 600W -48VDC

Output					
+3.3V	+5V	+12V	-5V	-12V	+5VSB
25A	25A	45A	-	0.8A	3.5A
Input					
-36VDC...-72VDC					
MTBF					
120.000 h					
Dimensioni					
150x86x185 mm					