



FANLESS MINI COMPUTER

BCO-1000-ADLN-B_3L

Fanless Mini Computer with Intel® IoTG N97/Intel® Atom® x7835RE Processors, 1x DP, 1x HDMI, 2x COM, 3x LAN, 1x 2.5" Drive Bay

Features


- Support 12th Gen Intel® IoTG Alder Lake-N N97/Intel® Atom® x7835RE
- DDR5 4800 MT/s SO-DIMM. Max. 16GB
- Dual Independent Display by 1x Display Port, 1x HDMI
- 3x Intel® I225-V 2.5GbE LAN
- 1x 2.5" Drive Bay
- 1x M.2 B-Key (Default: 128GB SSD)
- 1x Dual SIM Socket
- 2x COM, 2x USB 3.2 Gen 2, 2x USB 2.0
- 12 to 36VDC Wide Range Power Input Supporting AT/ATX Mode
- Wide Operating Temperature 0°C to 50°C
- TPM 2.0 Supported
- CE, FCC Class A, UL 62368 Ed. 3




Specifications

System		Physical	
Processor		Dimensions (WxDxH)	192 x 140 x 68mm
• 12th Gen Intel® IoTG Alder Lake-N Processor N97, 4 cores, 12W • Intel Atom® x7835RE Processor, 8 cores, 12W		Construction	Extruded Aluminum with Heavy Duty Metal
System Chipset		Mounting Options	Wall Mounting DIN-Rail Mounting (Optional)
LAN Chipset			
2x Intel® I225-V 2.5GbE LAN			
1x Intel® I225-V 2.5GbE LAN (Co-lay I226-LM Support TSN, not verified in NPI)			
Audio Codec			
Realtek ALC897			
System Memory			
DDR5 4800 MT/s SO-DIMM. Max. 16GB			
Graphics			
Intel® UHD Graphics			
BIOS			
AMI UEFI BIOS			
Watchdog			
Software Programmable Supports 1~255 sec. System Reset			
TPM			
TPM 2.0			
Display			
Display Port			
1x DisplayPort 1.4a			
Max Resolution 4096 x 2304 @60Hz			
HDMI			
1x HDMI 1.4b			
Max Resolution 3840 x 2160 @30Hz			
Multiple Display			
2x Independent Displays			
Storage			
SATA			
1x Internal 2.5" SATA SSD Bay (7mm or 9mm)			
Expansion			
M.2 B-Key			
1x M.2 B Key (2242/3042, SATA/PCIe x1/USB3.0, support LTE/4G/5G/Storage Module)			
M.2 E-Key			
1x M.2 E Key (2230, PCIe x1 & USB 2.0, support Wi-Fi & BT)			
I/O			
Audio			
Line-in/Line-out/Mic-in			
COM			
2x DB9			
COM1: RS232/422/485			
COM2: RS232			
GPIO			
1x 8 GPIO			
LAN			
3x RJ45 (2.5GbE)			
USB			
2x USB 3.2 Gen1			
2x USB 2.0 Type-A			
Others			
• 5x Antenna Holes • 1x Power button • 1x HD LED • 1x Power LED			
Operating System			
Windows			
Windows 10/11			
Linux			
Linux Kernel			
Power			
Power Adapter			
Optional AC/DC 12V/5A, 60W			
Power Mode			
AT, ATX (Default ATX)			
Power Supply Voltage			
12~36VDC			
Power Connector			
3-pin Terminal Block			
Environment			
Operating Temperature			
0°C to 50°C (12W CPU)			
Storage Temperature			
-30°C to 85°C			
Relative Humidity			
10% to 95% (non-condensing)			
Certification			
UL 62368 Ed. 3, CE, FCC Class A			
Vibration			
With SSD: 5 Grms (5 - 500 Hz, 0.5 hr/axis)			
Shock			
With SSD: 50G half-sin 11ms			

External I/O Mechanical Layout




Front Panel



Rear Panel

Dimension

Unit: mm



Compliances and Standards

Vibration	With SSD: 5 Grms (5 - 500 Hz, 0.5 hr/axis) IEC60068-2-64:2008 Designed to comply with MIL-STD-810H Method 514.8 Procedure I
Shock	With SSD: 50G half-sin 11ms IEC60068-2-27:2008 Designed to comply with MIL-STD-810H Method 516.8 Procedure I
Operating Temperature	0°C to 50°C (12W CPU) IEC60068-2-1:2007 (Cold test procedure) IEC60068-2-2:2007 (Dry heat test procedure) IEC60068-2-3:2007 (Damp heat, steady state, test procedure) IEC60068-2-14:2009 (Wide temperature range thermal shock)
EMC	- FCC Class A - CE - ICES-003 - UKCA - Industrial EMC Compliance - EN 61000-4-2: 2009 - EN IEC 61000-4-3: 2020 - EN 61000-4-4: 2012 - EN 61000-4-5: 2014 +A1: 2017 - EN 61000-4-6: 2014
Safety	- UL Safety: UL62368-1, 3rd Ed., (cULus) - Test procedure: CB Scheme - Standard: IEC 62368-1:2018

Available Models

Model No.	Description
BCO-1000-ADLN-B-N97-3L	Fanless Mini Computer with Intel® IoTG N97 Processors, 1x DP, 1x HDMI, 2x COM, 3x LAN, 1x 2.5" Drive Bay
BCO-1000-ADLN-B-X7835RE-3L	Fanless Mini Computer with Intel® Atom® x7835RE Processors, 1x DP, 1x HDMI, 2x COM, 3x LAN, 1x 2.5" Drive Bay
BCO-1000-ADLN97-3L-P	Fanless Mini Computer with Intel® IoTG N97 Processors, 1x DP, 1x HDMI, 2x COM, 3x LAN, 1x 2.5" Drive Bay, w/ Power Adapter
BCO-1000-ADLX7835RE-3L-P	Fanless Mini Computer with Intel® Atom® x7835RE Processors, 1x DP, 1x HDMI, 2x COM, 3x LAN, 1x 2.5" Drive Bay, w/ Power Adapter

Optional Accessories

Model No.	Description
1-E09A06008	Adapter AC/DC 12V 5A 60W with 3pin Terminal Block Plug 5.0mm Pitch
1-TPCD00005	Power Cord, 3-pin US Type, 180cm
1-TPCD00002	Power Cord, European Type, 180cm
1-TPCD00001	Power Cord, 3-pin UK Type, 180cm
3-DINR-0004	Din Rail-2 Mounting Kit

Packing List

1x BCO-1000-ADLN-B Fanless Mini Computer
1x Wall Mount Kit
1x Adapter 60W 12V 5A (selected models only)

US Exports And Tariff Codes

ECCN	5A992.c
HTS	8471.50.0150
ScheduleB	84.71

Premio Inc.

918 Radecki Ct., City of Industry
CA 91748, United States
Toll Free: 800.977.3646

Premio Taiwan Inc.

18F, No.176, Jianyi Road, Zhonghe District,
New Taipei City 235603, Taiwan
Toll Free: 886.2.7731.7888

Email: sales@premioinc.com
Website: <https://premioinc.com>