



Model (left side open)	Model (right side open)
X124	X124R

Benefits

- ▶ 1U 24.1" LCD console drawer
- ▶ 1920 x 1200 **WUXGA** native resolution / 16.7M colors
- ▶ HDMI 1.4 + VGA video input / USB KB / MS
- ▶ 104-key USB keyboard with either touchpad or trackball
- ▶ One Man installation design
- ▶ Enhanced aesthetics with new molded front panel and 2-pt lock
- ▶ 2-year standard warranty (upgradable up to 5 years)
- ▶ TAA Compliant

Options

- Dual stereo speakers for HDMI (**HS4.4**)
- DP + Speakers (**DP**)
- DVI-D + Audio + Speakers (**DV4.4**)
- 3G / HD / SD-SDI Broadcast-grade input + Speakers (**SDI**)
- Front USB hub port for device access (**USB**)
- DC power : 12V / 24V / 48V / 125V / 250V
- Touchscreen : Resistive 1-pt

Product Specifications

Console Port

Video input	HDMI 1.4 + VGA
KB / MS	USB interface
VGA console 6ft cable : CB-6A	Drawer end : DB-15 + USB type A x 2
or	Server end : DB-15 + USB type A x 2
HDMI console 6ft cable : CX-6B	Drawer end : HDMI + USB type A x 2
	Server end : HDMI + USB type A x 2

LED-backlit LCD Panel

Panel size (diagonal)	24.1"
Native resolution	1920 x 1200
Brightness (cd/m ²)	300
Contrast ratio (typ.)	1000 : 1
Colors	16.7 M
Viewing angle (L/R/U/D)	89/89/89/89
Response time (ms)	14
Dot pitch (mm)	0.27
Display area (mm)	518.4H x 324V
Surface treatment	Anti-glare, Hard-coating
Surface hardness	3H
Backlight type	LED
MTBF (hrs)	30,000

Physical

Product (W x D x H)	Single console	442 x 690 x 44 mm 17.4 x 27.2 x 1.73 inch
	Console w/ KVM	442 x 800 x 44 mm 17.4 x 31.5 x 1.73 inch
Packing (W x D x H)	Single console /	590 x 965 x 136 mm
	Console w/ KVM	23.2 x 38 x 5.4 inch
Net weight	Single console	15.3 kg / 33.7 lb
	Console w/ KVM	16.1 kg / 35.4 lb
Gross weight	Single console	19.5 kg / 42.9 lb
	Console w/ KVM	22 kg / 48.4 lb

* All dimensions stated are subject to change if options are selected / integrated to base model part codes

Mounting Distance

Single console drawer	660 ~ 890 mm 26 ~ 35 inch
Console w/ KVM drawer	660 ~ 970 mm 26 ~ 38.2 inch

Video Option

Digital	DVI-D	DVI-D single link
	DisplayPort	DP 1.0 / HDCP 1.3

Power

Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption (console / KVM)	Screen on	Max. 33W / Max. 65W
	Power saving mode	Max. 2W / Max. 30W
	Power button off	Max. 1W / Nil

Environment

Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	10~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	10~300Hz 0.5G RMS random vibration

Compliance

EMC	FCC & CE
Safety	CE / LVD & UKCA
Environment	REACH & RoHS3 / WEEE

X124 models w/ KVM

** Resolution related to LCD specification

For right side open - Add **R** at the end of the model no.
sample : X124-MUIP3224**R**

HDMI KVM		Remote	8-port
	0	0	X124 - 801K

HDMI KVM Cable


CK - 6H (6 ft)
4K HDMI - HDMI cable


CK - 6P (6 ft)
4K HDMI - DP cable


CH - 6D (6 ft)
2K HDMI - DVI-D cable

DP KVM		Remote	8-port
	0	0	X124 - 801DP

DP USB KVM Cable

Resolution 16:9 - max. 3840 x 2160
Support ** : 16:10 - max. 1920 x 1200


CK - 6DP (6 ft)
4K DP - DP cable

DVI-D KVM		Remote	12-port
	0	0	X124 - 1201D

DVI-D USB KVM Cable

Resolution 16:10 - max. 1920 x 1200
Support ** : 16:9 - max. 1920 x 1080
4:3 - max. 1600 x 1200


CI - 6 (6 ft)
CI - 15 (15 ft)

Cat6 Matrix KVM		Remote	8-port	16-port	32-port
	1	1	-	X124 - MUIP1613	X124 - MUIP3213
	2	1	-	X124 - MUIP1624	X124 - MUIP3224
	0	1	-	X124 - MU1602	X124 - MU3202
	0	2	-	X124 - MU1603	X124 - MU3203
	0	3	-	X124 - MU1604	X124 - MU3204

Cat6 KVM Dongle


DG - 100C
USB-C dongle


DG - 100P
DP - USB dongle


DG - 100H
HDMI - USB dongle


DG - 100SD
DVI - USB dongle


DG - 100S
VGA - USB dongle

Resolution 16:10 - max. 1920 x 1200
Support ** : 16:9 - max. 1920 x 1080
4:3 - max. 1600 x 1200

Cat6 Combo KVM		Remote	8-port	16-port	32-port
	1	0	X124 - UIP802	X124 - UIP1602	X124 - UIP3202
	0	1	X124 - U802	X124 - U1602	X124 - U3202
	0	0	X124 - U801	X124 - U1601	X124 - U3201

DB-15 Combo KVM		Remote	8-port	16-port
	1	0	X124 - IP802	X124 - IP1602
	0	1	X124 - 802	X124 - 1602
	0	0	X124 - S801	X124 - S1601

DB-15 VGA USB KVM Cable


CB - 6 (6 ft)


CB - 10 (10 ft)



CB - 15 (15 ft)


Resolution 16:10 - max. 1920 x 1200
Support ** : 16:9 - max. 1920 x 1080
4:3 - max. 1600 x 1200

DB-15 USB Hub KVM		Remote	8-port
	1	0	X124 - IP802H
	0	1	X124 - 802H
	0	0	X124 - 801H


Standard Keyboard


 G keyboard with touchpad





 G keyboard with trackball





Supporting layouts

America U.S.

EMEA

 U.K.

 Germany

 France

 Spain

 Italy

Asia

 Japan

 Korea