


# GAP-351P - G6 Series 3U RUGGED WORKSTATION



Intel® Xeon® E3-1200 v5/v6, Intel® 6th/7th Gen. Core™ i7/i5/i3 series - Kaby Lake / Sky Lake  
Front I/O - Front Power Supply



**GAP** is a line of rugged servers and workstations with aluminum construction, designed for applications that require a robust and qualified MIL-GRADE device, suitable for operating in critical environments.

GAP-351P G6 series workstations features Intel® Xeon® E3-1200 v5/v6, Intel® 6th/7th Gen. Core™ i7/i5/i3 series (Kaby Lake / Sky Lake) processors supporting up to 4 Cores (8 thread with Hyper-Threading), 8MB Smart Cache, up to 64GB DDR4 memory with our without ECC and up to 16 PCIe 3.0 lanes. The integrated IPMI services support monitoring, control, and management functions and provides for alarm notifications in case of critical events.

GAP-351P is designed for 19" rackmounting and has a 3U chassis with 510mm depth.

The front I/O and power supply layout includes all the connectors on the front of the chassis as required for front only installations.

GAP-351P rugged workstation includes up to three removable SSD, three internal SSD and an optional slim DVD. The unit may host up to five full height / full length PCIe cards.

The additional boards are equipped with dedicated fixing systems to ensure optimal operation even in the presence of shock and vibration or during transport.

GAP workstations are qualified according to MIL-STD-810G for temperature, shock and vibration and can optionally conform to MIL-STD-461 for EMI /EMC. Upon request, the integrated devices, complete with I / O cards, can be subjected to specific profiles of thermal or mechanical stress. Versions with MIL grade connectors on I/O ports and power input are available.

All units are delivered with their inventory list to ensure configuration control and reproducibility over time.

## FEATURES

- 3U Rugged Workstation - 510mm depth
- Single Intel® Xeon® E3-1200 v5/v6 series
- Single Intel® 6th/7th Gen. Core™ i7/i5/i3 series
- Front I/O connectors
- Front Power Input
- Redundant AC or DC Power Supply
- Up to 3 removable 2.5" SSD + 3 x internal 2.5" SSD
- Optional DVD
- Up to 5 PCIe boards
- Optional Conformal Coating
- MIL-STD-810G
- Optional MIL-STD-461

## Technical Specifications

### System

<b>Processor</b>	Intel® Xeon® E3-1200 v5/v6, Intel® 6 <sup>th</sup> /7 <sup>th</sup> Gen. Core™ i7/i5/i3, Intel® Celeron® and Intel® Pentium®
<b>Memory</b>	Up to 64GB ECC/non-ECC UDIMM, DDR4-2400MHz
<b>Chipset</b>	Intel® C236
<b>Network</b>	1 x GbE LAN with Intel® i210-AT 1 x GbE LAN with Intel® i219lm
<b>Storage</b>	6 SATA3 (6Gbps) ports; RAID 0, 1, 5, 10
<b>TPM</b>	1 TPM Header
<b>Motherboard I/O</b>	Available on the front: 1 x VGA, 2 x USB 2.0, 2 x USB 3.0, 2 x LAN, 1 x HDMI, 1 x DVI, Audio
<b>Expansion slots</b>	3 PCI-E 3.0 x16 (run at 16/NA/16 or 16/8/8), 1 PCI-E 3.0 x1 (in x4) 1 5V PCI 32-bit slot Interface M.2: 1 PCI-E 3.0 x4 Form Factor: 2242/2260/2280 - Key: M-Key
<b>Operative Systems</b>	Windows® 7, Windows® 8.1, Windows® 10 IoT Enterprise 2016, Windows® Server 2008 R2, Windows® Server 2012 R2, Windows® Server 2016, Linux
<b>IPMI</b>	IPMI2.0, SPM, Watchdog; SNMP and e-mail alarms and notifications
<b>Monitoring</b>	Monitoring, control, and management functions (fan speed, temperature, voltage, redundant power failure, power consumption, disk health, raid health, and memory health)

### Power Supply

<b>Power Supply</b>	100/240 Redundant VAC 18-36 Single or Redundant VDC 36-72 Single or Redundant VDC
---------------------	---

### Mechanical

<b>Dimensions</b>	483 x 133 x 510 mm
<b>Construction</b>	Aluminum with surface passivation treatment
<b>Colour</b>	Silver
<b>Mounting</b>	3U 19" rackmount chassis Telescopic slides optional
<b>Configuration</b>	Front I/O and Power Supply
<b>Front Panel</b>	Led: Led Power ON and HDD/SSD functionality; Switch: Power ON / OFF and System Reset; Connectors: 2x USB 2.0
<b>Drive Bay</b>	1 x slim 5.25"; 1 x 3.5" bay + 1 x internal bay x 3 ODD 2.5"

### Environmental - (Design to meet)

<b>Operative Temperature</b>	Standard: 0°C / +50°C Extended: -20°C / +60°C (depending on the configurations)
<b>Operative Humidity</b>	8% to 95% non-condensed (depending on the configurations)
<b>Storage Temperature</b>	-40°C / +70°C
<b>Vibrations</b>	MIL-STD-810G, Method 514.7, Cat 4 - Proc. I - 2.24 Grms, 5-500 Hz 60 min/axis for 3 axes
<b>Operative Shock</b>	MIL-STD-810G Proc. I Method 516.7 - 15g / 11ms - half sine
<b>Transport shock</b>	MIL-STD-810G Proc. II Method 516.7 - 30g / 9ms sawtooth
<b>Certifications</b>	Directive 2014/35/UE-LVD / Directive 2014/30/UE-EMC Directive 2011/65/UE - RoHS / Regulation (EC) No 1907/2006 - REACH

GAP servers and workstations are designed in accordance with the environmental specifications indicated. Some parameters depend on the configuration. Equipment may be subjected to dedicated test profiles.