



## SERVAL RD15-FHD-02

# FULL-RUGGED 15.6" DISPLAY

All rugged roda RD series displays are MIL-STD810, MIL-STD461, and  $\geq$  IP54 certified for use under almost all environmental conditions. As a standard model, they can operate under a temperature range of  $-20^{\circ}\text{C}$  to  $+55^{\circ}\text{C}$ . With its remote on/off function button/interface and metal housing, the RD series is particularly suitable when combined with a roda computer as well as for installation in protected and armoured vehicles and cabins that, due to space constraints, require a decentralised installation of computer and display. The system can be started at the touch of a button on the display. The perfect conditions for efficient operation!

The compact 15.6" Panel display RD15-FHD is available in different versions and can also be customised with military connectors. The displays with and without touch screen, high brightness, picture-in-picture, as well as blackout light and NVIS functionality are frequently used under tough conditions.

- + Full-HD LCD (1920x1080 pixel)
- + Typ. Brightness 800 cd/m<sup>2</sup>
- + **OPTIONAL:** resistve touch screen
- + IP65
- + MIL-STD-810G
- + MIL-STD-461G



# RD15-FHD-02

## + DISPLAY

LCD 15.6" FHD (1920x1080)  
LED backlight

## + FORMAT

16:9

## + TOUCH

+ **OPTIONAL:** resistive touch screen

## + CONTRAST

750:1

## + BRIGHTNESS

typ. 800 cd/m<sup>2</sup>

## + COLOR REPRESENTATION

Up to 16.7 million (8 bit/colors)

## + VIEWING ANGLE

vertical: ±160 °  
horizontal: ±160 °

## + REACTION TIME

30 ms (T<sub>ON</sub>+T<sub>OFF</sub>)

## + INTERFACES

2x USB2.0  
1x VGA  
1x DVI (with roda display remote)  
1x MIL DC-In  
(with integrated camouflage function)  
+ **OPTIONAL:**  
1x USB2.0 (front side)  
All connectors also available MIL version!

## + KEYS

8x programmable function keys

## + FUNCTIONS

Camouflage mode  
NVIS compliant  
+ **OPTIONAL:**  
PiP - picture in picture

## + POWER SUPPLY

18-32 V<sub>DC</sub>, nominal 24 V<sub>DC</sub>  
Power consumption < 30 W  
Transient protection according to VG96916  
T5 without intermittent operation

## + DIMENSIONS [W×H×D]

393 x 270 x 66 mm

## + WEIGHT

4.80 kg

## + PROTECTION CLASS

IP65

## + ACCESSORIES

- rugged IP65 AC-adaptor AC90
- rugged DC/DC-converter ROD01.2
- rugged transportation box
- rugged mounting systems
  - e.g. RD15 StandUnit
  - custom mounting on request
- Shockmount fixation, designed to meet MIL-STD-810G

MIL-STD-810G	OPERATING	STORAGE
TEMPERATURE	-30 °C to +65 °C	-20 °C to +70 °C
HUMIDITY	N/A	95%

  

EMI	OPTIONAL
MIL-STD-461G	Ground Navy



### CUSTOMIZATION:

Need anything not included in the data sheet? roda products are designed to enable customization to your specific program requirements. Please contact your roda sales team member to find the best solution for your requirements.

roda computer GmbH reserves the right to change without notice the information.

**roda**  
solid IT-solutions

www.roda-computer.com