



- 105 keys, short travel
- 38 mm trackball
- stainless steel housing
- IP65 sealing

FOOD KEYBOARD WITH TRACKBALL

This "food" keyboard is specifically adapted to the harsh conditions in food processing industry. The combination of cold environment and hot cleaning water/damp creates one of the most challenging environments for electronic HMI devices. Touchscreen might seem like the perfect solution, but has its limits towards ergonomics and usability. Designed around a new concept that integrates the experience NSI has built up in this market throughout the years, we are introducing a number of innovations that will result in a very reliable and stable solution.

MAIN FEATURES

- All stainless steel enclosure, sealed to IP65
- Integration of a waterproof breathable membrane on the backside, creating a dry environment inside the enclosure
- Design optimized to reduce contamination.
- Integrated 38 mm trackball, IP68 and easily cleanable
- Short travel switches of 0,3 mm with low pressure of 2.55N for increased speed typing
- Positive tactile feedback and key embossing
- Optimum legending colour scheme and contrast
- User-friendly layout with separate numerical-, control- and function keypads
- Dimensions / weight: 475 x 200 x 58 mm / 3,1 kg

Typical applications

Food industry – automation
Breweries
Industrial bakeries
Vegetable processing plants
Meat processing plants
System integrators specialised in this market
Restaurant applications
and much more...

GENERAL TECHNICAL SPECIFICATIONS

Sealing : IP65 sealed

Keys : 105 short travel keys

Pointing Device : 38 mm waterproof laser trackball

Operating temperature : 0°C to +60°C

Output : detachable 2m. shielded USB cable,

IP68, ended by a type A connector

Housing : stainless steel

Front layer : polyester, chemical resistant Supply voltage : +5V +/- 5% (via keyboard port)

Supply current : 200mA max.


ORDER INFO

| COUNTRY LAYOUT | |
|------------------|-------------------|
| US Qwerty | KSTM105RVS0001USB |
| Cyrillic Russian | KSTM105RVS0007USB |
| Belgian Azerty | KSTM105RVS0032USB |
| French Azerty | KSTM105RVS0033USB |
| Norwegian Qwerty | KSTM105RVS0047USB |
| German Qwertz | KSTM105RVS0049USB |













The company reserves the right to alter without prior knowledge the specification or design of any standard product or service.